

INTER•PAK SERIES SC-200 Stationary Compactor

See for yourself how we crush the competition!

FEATURES & SPECS

CHARGE BOX

CYCLE TIME: EXT: 40 SEC REC: 35 SEC OPENING: 41" L X 60" W SIDES: 3/16" THICK WITH STRUCTURAL SUPPORTS FLOOR: 3/8" THICK PLATE WITH 4" CHANNEL CROSSMEMBERS BREAKER BAR: 6" X 8" X 1"

RAM

FACE PLATE: 3/8" THICK WITH 6" CHANNEL CROSSMEMBERS BOTTOM: 3/8" THICK SIDES: 1/4" THICK TOP: 1/4" THICK WITH 4" CHANNELS GUIDES: REPLACEABLE 3 POINT NYLATRON GUIDES PENETRATION: 15" NORMAL FORCE: 50,800 LBS MAX FORCE: 56,500 LBS RAM FACE PRESSURE: NORMAL: 29.9PSI MAX: 33.2 PSI

ELECTRICAL

MOTOR: 10 HP 3/60-208/230/460 VAC CONTROL VOLTAGE: 120 VAC 15' REMOTE PENDANT WITH 4 BUTTON STATION 15' REMOTE COLOR-CODED PRESSURE GAUGE KEY AUTO/HAND, EMERGENCY STOP WITH LIGHT, START, FOR/REV 100% LIGHT, 15' POWER PIG TAIL





YEAR



INTER•PAK SERIES SC-200 Stationary Compactor



RESERVOIR CAPACITY: 28 GALLONS PUMP: 10.5 GPM NORMAL PRESSURE: 1800 PSI MAX PRESSURE: 2000 PSI HYDRAULIC CYLINDER: BORE: 6" ROD: 2.5" STROKE: 56"

AVAILABLE OPTIONS

PREMIUM POWER UNIT 80% FULL LIGHT HEAVY DUTY CYLINDER OIL TANK HEATER DOOR COUNTER SYSTEM LOW TEMPERATURE OIL MONITORING SYSTEM PHOTO ELECTRIC EYE DOG HOUSES, ENCLOSURES WALK ON DECK, DRIVE ON DECK FRONT VIEW

COLORS



*Color Match Available



