



INTER•PAK SERIES SC-300 Stationary Compactor

See for yourself how we crush the competition!



FEATURES & SPECS



CHARGE BOX

CYCLE TIME: 10 HP EXT: 46 SEC REC: 30 SEC
15 HP EXT: 26 SEC REC: 18 SEC
OPENING: 50" L X 60" W
SIDES: 3/16" THICK WITH STRUCTURAL SUPPORTS
FLOOR: 3/8" THICK PLATE WITH 4" CHANNEL CROSSMEMBERS
BREAKER BAR: 6" X 8" X 1"

RAM

FACE PLATE: 3/8" THICK WITH 6" CHANNEL CROSSMEMBERS
BOTTOM: 3/8" THICK
SIDES: 1/4" THICK
TOP: 1/4" THICK WITH 4" CHANNELS
GUIDES: REPLACEABLE 3 POINT NYLATRON GUIDES
PENETRATION: 15"
NORMAL FORCE: 50,800 LBS MAX FORCE: 56,500 LBS
RAM FACE PRESSURE: NORMAL: 29.9PSI MAX: 33.2 PSI

ELECTRICAL

MOTOR: 10 HP 3/60-208/230/460 VAC
15HP 3/60-208/230/460 VAC
CONTROL VOLTAGE: 120 VAC
15' REMOTE PENDANT WITH 4 BUTTON STATION
15' REMOTE COLOR-CODED PRESSURE GAUGE
KEY AUTO/HAND, EMERGENCY STOP WITH LIGHT, START, FOR/REV
100% LIGHT, 15' POWER PIG TAIL



INTER-PAK SERIES SC-300 Stationary Compactor

HYDRAULIC

RESERVOIR CAPACITY: 10 HP 28 GALLONS

15 HP 40 GALLONS

PUMP: 10 HP: 10.5 GPM

15 HP: 18 GPM

NORMAL PRESSURE: 1800 PSI MAX PRESSURE: 2000 PSI

HYDRAULIC CYLINDER:

BORE: 6" ROD: 3.5" STROKE: 65"

AVAILABLE OPTIONS

PREMIUM POWER UNIT

80% FULL LIGHT

HEAVY DUTY CYLINDER

OIL TANK HEATER

DOOR COUNTER SYSTEM

LOW TEMPERATURE OIL

MONITORING SYSTEM

PHOTO ELECTRIC EYE

DOG HOUSES, ENCLOSURES

WALK ON DECK, DRIVE ON DECK

COLORS



**Color Match Available*

