



INTER•PAK SERIES SC-400 Stationary Compactor

See for yourself how we crush the competition!



FEATURES & SPECS



CHARGE BOX

CYCLE TIME: 15 HP EXT: 33 SEC REC: 19 SEC
20 HP EXT: 33 SEC REC: 19 SEC
OPENING: 66" L X 60" W
SIDES: 3/16" THICK WITH STRUCTURAL SUPPORTS
FLOOR: 3/8" THICK PLATE WITH 4" CHANNEL CROSSMEMBERS
BREAKER BAR: 6" X 8" X 1"

RAM

FACE PLATE: 3/8" THICK WITH 6" CHANNEL CROSSMEMBERS
BOTTOM: 3/8" THICK
SIDES: 1/4" THICK
TOP: 1/4" THICK WITH 4" CHANNELS
GUIDES: REPLACEABLE 3 POINT NYLATRON GUIDES
PENETRATION: 15"
NORMAL FORCE: 50,800 LBS MAX FORCE: 56,500 LBS
RAM FACE PRESSURE: NORMAL: 29.9PSI MAX: 33.2 PSI

ELECTRICAL

MOTOR: 15 HP 3/60-208/230/460 VAC
20 HP 3/60-208/230/460 VAC
CONTROL VOLTAGE: 120 VAC
15' REMOTE PENDANT WITH 4 BUTTON STATION
15' REMOTE COLOR-CODED PRESSURE GAUGE
KEY AUTO/HAND, EMERGENCY STOP WITH LIGHT, START, FOR/REV
100% LIGHT, 15' POWER PIG TAIL

HYDRAULIC

RESERVOIR CAPACITY: 28 GALLONS
 PUMP: 15 HP: 18 GPM
 20 HP: 18 GPM
 NORMAL PRESSURE: 1800 PSI MAX PRESSURE: 2000 PSI
 HYDRAULIC CYLINDER:
 BORE: 6" ROD: 4" STROKE: 82"

AVAILABLE OPTIONS

PREMIUM POWER UNIT
 80% FULL LIGHT
 HEAVY DUTY CYLINDER
 OIL TANK HEATER
 DOOR COUNTER SYSTEM
 LOW TEMPERATURE OIL
 MONITORING SYSTEM
 PHOTO ELECTRIC EYE
 DOG HOUSES, ENCLOSURES
 WALK ON DECK, DRIVE ON DECK

COLORS



**Color Match Available*

