



Inter Pak Self-Contained Compactors



FEATURES & SPECS

BODY

- 7 GA FLOOR & LOWER SIDE SHEETS
- 10GA TOP SIDE WALLS & ROOF
- 16" CENTERS CROSSMEMBER SPACING
- 1/4" MAIN RAILS
- 1/4" MAIN RAIL WEAR STRIPS
- 4" X 6" SOLID STEEL ROLLERS
- SINGLE RATCHET LOCK SYSTEM
- MACHINED DOUBLE

CHARGE BOX

- 1/4" SIDES, 3/8" FLOOR
- 44" STANDARD LOAD HEIGHT
- 6" X 8.2 LB CHANNEL SIDE STIFFENER
- CLEAR TOP OPENING (41" X 60")
- 4 RETAINING TEETH
- CAPACITY: (MFRS RATING) 2 CUBIC YARD

RAM

- 7G TOP, 1/4" SIDES, 3/8" FACE, 1/2" BOTTOM
- NORMAL FORCE: 39,950 LBS
- MAX FORCE: 49,550 LBS
- PENETRATION: 6"

ELECTRICAL

- MOTOR: 208/230 460 10 HP
- CONTROL VOLTAGE: 120 VHC
- PLC CONTROLLED
- 15 LIQUID TIGHT CONDUIT FOR PENDANT
- SINGLE & MULTI-PHASE POWER UNITS AVAILABLE

HYDRAULIC

- INTERNAL BYPASS CYLINDERS (SINGLE & SCISSOR AVAILABLE)
- NORMAL PRESSURE: 1,850 PSI
- MAX PRESSURE: 2,000 PSI
- 25 GAL OIL RESERVOIR
- 10.5 GPM PUMP

Contact:
sales@crarent.com
service@crarent.com



Give us a call
(855) 898-4811

CRARENT.COM





Contact:
sales@crarent.com
service@crarent.com



Give us a call
(855) 898-4811

CRARENT.COM



STANDARD FEATURES

- HINGED BREAKER BAR TEETH
- OPEN & EASILY ACCESSIBLE CHARGE BOX
- BOTH SIDES PORTED
- INCLUDES 10' HYDRAULIC HOSE WITH QUICK DISCONNECT
- AVAILABLE IN NON-INTERNAL BYPASS
- REPLACEABLE NO MAINTENANCE UHMW SHOE
- WEAR RESISTANT/LONG LASTING
- EASY TO REPLACE GUIDE

COLORS

*COLOR MATCH AVAILABLE



STANDARD POWER FEATURES

- 15' COLOR PRESSURE GAUGE
- 15' REMOTE PENDENT
- 30MM ALLEN BRADLEY PUSH BUTTONS
- KEY OPERATED AUTO/ OFF/ MANUAL RUN
- ALLEN BRADLEY PLC, MOTOR STARTER, OVERLOAD
- 80% & 100% FULL LIGHT
- RUNS PRESSURE AND TIMING UNITS
- NEMA 4 ENCLOSURE

POWER UNIT OPTIONS

- OIL HEATER
- DOOR COUNTER SYSTEM
- PHOTO EYE SYSTEM
- SINGLE PHASE VFD POWER UNITS
- ODOR CONTROL
- LOW TEMP OIL

DIMENSIONS

STANDARD SIZES	OVL
34 YARD SCC	276"
30 YARD SCC	250"
25 YARD SCC	222"
20 YARD SCC	204.25"
15 YARD SCC	174.25"

*CUSTOM SIZES BUILT TO ORDER

*DIMENSIONAL DRAWING AVAILABLE

